

# Model: 752

## Cast Iron Flanged End Y Type Strainers Size: 1½" - 24" (40 - 600mm)

Working Pressure - Non-Shock ANSI B16.1	
	CWP
1½" - 12"	500psi @ 150°F
14" - 24"	200psi @ 150°F
	Steam
1½" - 12"	250psi @ 450°F
14" - 24"	200psi @ 406°F

752

Class 250



Model 752

### Typical Service

- Used extensively to strain foreign matter from pipe lines and provide economical protection for costly pumps, meters, valves, and other similar mechanical equipment

### Features

- Mueller "Breech-Lok Strainers"
  - Furnished as standard in sizes 8" and larger.
    - A one quarter-turn securely locks the screen in its seat.
    - Allows for easy bolting of the cover flange.
  - Tapered seats in both the body and cover flange retain screen and prevent particle bypass

### Construction

- Gasketed cover, O-ring seats available.

### Self-Cleaning

- Self-cleaning is accomplished by opening the plug or valve connected to the blowoff outlet

### Blowoff Outlets

- Outlets are NPT tapped
- Sizes of tapping specified on next page.
- Not normally furnished with plug. Plug available, specify with order

### Capacity

- Generously proportioned bodies
- Open Area Ratio much greater than pipe size, ensuring low pressure drop.

### Screens

MODEL	SIZES	STANDARD (WATER)		STEAM RECOMMENDATION	
		MATERIAL	OPENING	MATERIAL	OPENING
752	1½" - 4"	304SS	.062" perf	304SS	.045" perf
	5" - 10"	304SS	.125" perf	304SS	.045" perf
	10" & Up	304SS	.125" perf	304SS	.062" perf

Job Name \_\_\_\_\_

Job Location \_\_\_\_\_

Engineer \_\_\_\_\_

Approval \_\_\_\_\_

Contractor \_\_\_\_\_

Approval \_\_\_\_\_

Contractor's P.O. No. \_\_\_\_\_

Representative \_\_\_\_\_

## Materials


752	
Body	Cast Iron ASTM A126-B
Cover	A126-B 1½" - 5", A516-70 Plate 6" & Up
Gasket	Compressed Fiber

## Pressure Drop

See Pressure Drop Charts in Technical Data section of the Mueller Steam Engineering binder.

## Dimensions and Weights

SIZE		DIMENSIONS						WEIGHT	
		A		B		C			
in.	mm	in.	mm	in.	mm	in.	mm	lbs.	kgs.
1½	40	8 <sup>1</sup> / <sub>16</sub>	204	4 <sup>3</sup> / <sub>4</sub>	121	½	15	24	10.9
2	50	9 <sup>5</sup> / <sub>16</sub>	237	6	152	½	15	26	12
2½	65	11 <sup>1</sup> / <sub>16</sub>	281	7 <sup>1</sup> / <sub>8</sub>	181	1	25	40	18
3	80	12 <sup>5</sup> / <sub>8</sub>	321	9 <sup>1</sup> / <sub>8</sub>	232	1¼	32	59	26.8
3½	90	14 <sup>3</sup> / <sub>8</sub>	365	9	229	1¼	32	76	34
4	100	15 <sup>5</sup> / <sub>8</sub>	397	10 <sup>7</sup> / <sub>8</sub>	276	1½	40	93	42
5	125	18¼	464	12 <sup>15</sup> / <sub>16</sub>	329	2	50	146	66
6	150	20 <sup>3</sup> / <sub>16</sub>	512	14½	368	2	50	194	88
8	200	25 <sup>1</sup> / <sub>8</sub>	638	16 <sup>7</sup> / <sub>16</sub>	418	2	50	316	143
10	250	29 <sup>1</sup> / <sub>8</sub>	739	21	533	2	50	475	215
12	300	33 <sup>3</sup> / <sub>4</sub>	857	25	635	2	50	750	3740
14	350	38 <sup>3</sup> / <sub>4</sub>	984	28 <sup>3</sup> / <sub>4</sub>	730	2	50	908	412
16	400	44 <sup>1</sup> / <sub>8</sub>	1128	29 <sup>5</sup> / <sub>8</sub>	752	2	50	1135	515
18	450	47 <sup>3</sup> / <sub>4</sub>	1213	34 <sup>11</sup> / <sub>16</sub>	881	2	50	2400	1090
20	500	56	1422	39	991	2	50	3350	1522
24	600	57½	1461	45	1143	2	50	4705	2138



Model 752

Apply for Certified Drawings.

Mueller Steam Specialty product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Mueller Steam Specialty Technical Service. Mueller Steam Specialty reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Mueller Steam Specialty products previously or subsequently sold.



A Watts Water Technologies Company

ES-MS-752 1020

